

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
OF T. 16 N., R. 37 E.

CHAINS

80.00

Point for the 80 1/16 sec. cor. of secs. 7 and 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T16N R37E} \\ 1/16 \frac{\text{S } 7}{\text{S } 18} 80 \end{array}$$

1966

raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

80.90

Drift fence, same, bears SE. and NW.

81.20

Wash, 15 lks. wide, 2 ft. deep, drains SE.; asc. 50 ft. along a gently rolling N. slope.

87.07

Intersect the E. bdy. of T. 16 N., R. 36 E.

Point for the closing cor. of secs. 7 and 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T16N} \\ \text{R36E} \mid \text{R37E} \\ \text{S } 12 \mid \frac{\text{S } 7}{\text{S } 18} \text{ CC} \end{array}$$

1966

from which

A pinon, 8 ins. diam., bears N. 76° E., 41 lks. dist., mkd. T16N R37E S7 CC BT.

A juniper, 10 ins. diam., bears S. 42½° E., 82 lks. dist., mkd. T16N R37E S18 CC BT.

Raise a mound of stone, 3½ ft. base, 2½ ft. high, E. of cor.

from this corner

The cor. of secs. 12 and 13, T. 16 N., R. 36 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 16 N., R. 36 E., surveyed concurrently, bears SOUTH, 11.68 chs. dist.

The ¼ sec. cor. of sec. 12 only, T. 16 N., R. 36 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 16 N., R. 36 E., surveyed concurrently, bears NORTH, 28.32 chs. dist.