

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
OF T. 16 N., R. 37 E.

CHAINS	
28.70	Buffalo Canyon, 60 lks. wide, 14 ft. deep, drains NNW.
36.00	Wash, 40 lks. wide, 3 ft. deep, drains NNW.
37.40	Wash, 50 lks. wide, 7 ft. deep, drains NNW.
38.20	Wash, 10 lks. wide, 7 ft. deep, drains N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T16N R37E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{6}{7}$
	1966
	raise a mound of stone, $3\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of cor.
40.50	Abandoned drift fence, bears SSE. and NNW.; leave bottom land, bears SSE. and NNW. Asc. 20 ft. over an E. slope.
43.00	Wash, 50 lks. wide, 1 ft. deep, drains NE.; asc. 150 ft. over a continued E. slope.
67.30	Wash, same, drains ESE.; enter scattered timber, bears N. and S.; asc. 50 ft. over an E. slope.
74.10	Small wash, drains SE.; asc. 70 ft. over a gently rolling N. slope.
80.00	Point for the $80 \frac{1}{16}$ sec. cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T16N R37E $1/16 \frac{S}{S} \frac{6}{7} 80$
	1966
	from which
	A pinon, 4 ins. diam., bears N. 20° E., 31 lks. dist., mkd. X BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Asc. 70 ft. over a continued rolling N. slope.
86.96	Intersect the E. bdy. of T. 16 N., R. 36 E.
	Point for the closing cor. of secs. 6 and 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.