

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 37 E.

CHAINS	
11.90	Wash, 10 lks. wide, 2 ft. deep, drains SW.; asc. 20 ft. over a gradual WSW. slope.
18.20	Wash, 10 lks. wide, 2 ft. deep, drains WSW.; asc. a gradual WSW. slope.
20.50	Bladed dirt road, bears ENE. and WSW.; asc. a gradual WSW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd. <div style="text-align: center;"> T17N R37E $\frac{1}{4}$ S 5 S 4 1966 </div> Continue over a gradual WSW. slope.
49.40	Wash, 10 lks. wide, 4 ft. deep, drains WSW.; asc. a gradual WSW. slope.
63.70	Bladed dirt road, bears E. and W.; continue over a gradual WSW. slope.
72.50	Wash, 10 lks. wide, 2 ft. deep, drains W.; continue over a gradual W. slope.
80.77	Intersect the S. bdy. of sec. 33, T. 18 N., R. 37 E. Point for the closing cor. of secs. 4 and 5. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> T18N R37E S 33 S 5 S 4 T17N CC 1966 </div> raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor. From this corner The cor. of secs. 32 and 33, T. 18 N., R. 37 E., bears S. $89^{\circ} 59' W.$, 7.06 chs. dist. Land, gently rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush, shadscale and budsage.