

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 17 N., R. 37 E.

CHAINS	
	<p>Land, rolling to gently rolling. Soil, sandy clay and rocky. Undergrowth, shadscale, budsage and sagebrush.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8. N. 0° 03' W., bet. secs. 5 and 6. Over rolling land, through medium dense undergrowth.</p>
10.50	Low spur, slopes W.
12.60	Wash, 10 lks. wide, 1 ft. deep, drains W. 1 ch., thence SW.; asc. 30 ft. over a S. slope.
23.80	Flat topped ridge, bears NE. and SW.; desc. 30 ft. over a N. slope.
38.80	Wash, 10 lks. wide, 2 ft. deep, drains WSW.; asc. over a SE. slope.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T17N R37E $\frac{1}{2}$ S 6 S 5 1966</p>
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
	Asc. 130 ft. over a NE. slope.
60.00	Crest of ridge, bears NE. and SSW.; desc. 140 ft. over a N. slope.
77.70	Wash, 30 lks. wide, 4 ft. deep, drains NW.; asc. 30 ft. over a S. slope.
80.51	Intersect the S. bdy. of sec. 32, T. 18 N., R. 37 E. Point for the closing cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T18N R37E S 32. S 6 S 5 T17N CC 1966</p>