

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 9 N., R. 42 E.

CHAINS	
	Desc. 30 ft. over an E. slope.
46.70	Trail road, bears SSE. and NNW.; desc. 110 ft. over an E. slope.
74.20	Trail road, bears ENE. and WSW.; desc. 30 ft. over an E. slope.
84.25	The cor. of secs. 1 and 12, monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 9 N., R. 43 E.
	Land, rolling. Soil, sandy gravel. Undergrowth, shadscale.
	From the cor. of secs. 1, 2, 11 and 12.
	NORTH, on the sectional guide meridian, bet. secs. 1 and 2.
	Over rolling land, through medium undergrowth; asc. 10 ft. over a rolling E. slope.
2.70	Wash, 40 lks. wide, 2 ft. deep, drains E.; asc. 20 ft. over a rolling E. slope.
5.50	Trail road, bears E. and W.; asc. 60 ft. along a rolling E. slope.
22.00	Low spur, slopes E.; desc. 40 ft. along an E. slope.
31.20	Ravine, drains E.; asc. 30 ft. along an E. slope.
35.40	Trail road, bears E. and W.
40.00	Point for the ½ sec. cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T9N R42E ½ S 2 S 1
	1966
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Asc. 20 ft. along a rolling E. slope.
82.61	Point for the closing cor. of secs. 1 and 2, at an intersection with a line run WEST, from the cor. of secs. 35 and 36, T. 10 N., R. 42 E.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.