SURVEY OF THE SUBDIVISIONAL LINES, T. 29 N., R. 42 E.

59.60 Spur, slopes E.; desc. 30 ft. over an E. slope.
62.40 Ravine, drains SE.; asc. 70 ft. over a S. slope.
68.60 Spur, slopes E.; desc. 70 ft. over a NE. slope.
72.80 Ravine, drains E.; asc. 40 ft. over a SE. slope.
80.00 Point for the cor. of secs. 13, 14, 23 and 24.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T29N R42E S 14 S 13 S 23 S 24

1966

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.
Soil, loam, gravel and rocky.
Undergrowth, sagebrush and shadscale.

The $\frac{1}{4}$ sec. cor. of sec. 19, T. 29 N., R. 43 E., is monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. This cor. now refers to the $\frac{1}{4}$ sec. cor. of sec. 24, T. 29 N., R. 42 E., also, and the brass cap is remarked to read as follows:

T29N R42E R43E \$ 24 | S 19

1966 1959

The cor. of secs. 18 and 19, T. 29 N., R. 43 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. This cor. now refers to the cor. of secs. 13 and 24, T. 29 N., R. 42 E., also, and the brass cap is remarked to read as follows:

T29N R42E R43E S 13 S 18 S 24 S 19

> 1966 1959

From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.