SURVEY OF THE SUBDIVISIONAL LINES, T. 29 N., R. 42 E.

 	SURVEY OF THE SUBDIVISIONAL LINES, 1. 29 N., K. 42 E.
CHAINS	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Along a gently rolling W. slope.
75.20	Graded gravel road, bears NNE. and SSW.
77.30	Power line, bears N. 40° E. and S. 40° W.
81.42	The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent survey of T. 30 N., R. 42 E.
•	Land, gently rolling. Soil, loam, gravel and rocky. Undergrowth, shadscale.
•	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
	N. 0° 04' W., bet. secs. 32 and 33.
t	Over mountainous land, through medium undergrowth; desc. 90 ft. over a NW. slope.
8.20	Ravine, drains ESE.; asc. 110 ft. over a SE. slope.
18.30	Spur, slopes E.; desc. 170 ft. over a N. slope.
28.40	Wash, 50 lks. wide, 3 ft. deep, drains E.; asc. 210 ft. over a S. slope.
40.00	Point for the ½ sec. cor. of secs. 32 and 33.
,	Set an iron post, 28 ins. long, 2½ ins. diam., on an X on bedrock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.
	T29N R42E
	s 32 s 33
	1966
	Asc. 130 ft. over a S. slope.
45.50	Ridge, bears E. and W.; desc. 260 ft. over a NE. slope.
56.50	Ravine, drains NW.; asc. 50 ft. over a SW. slope.
65.70	Spur, slopes NW.; desc. 180 ft. over a rolling N. slope.
77.40	Ravine, drains NW.; asc. 40 ft. over a SW. slope.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap, $3\frac{1}{2}$ ft. base, with brass cap mkd.