•	SURVEY OF THE SUBDIVISIONAL LINES, T. 29 N., R. 42 E.
CHAINS	WEST, bet. secs. 19 and 30.
	Over nearly level land, through medium undergrowth.
0.50	Wash, 40 lks. wide, 5 ft. deep, drains NW.; desc. 10 ft. over a W. slope.
7.00	Trail road, bears ESE. and WNW.
	Desc. 30 ft. over a W. slope.
40.00	Point for the 2 sec. cor. of secs. 19 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T29N R42E 1/2 S 19 S 30
	1966
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Desc. 20 ft. over a W. slope.
62.10	Graded gravel road, bears NE. and SW.; desc. 10 ft. over a W. slope.
73.22	Intersect the E. bdy. of sec. 25, T. 29 N., R. 41 E.
	Point for the closing cor. of secs. 19 and 30.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
,	T29N R41E R42E S 25 S 19 CC S 30
	1966
*	raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	From this corner, the cor. of secs. 24 and 25, T. 29 N., R. 41 E., bears N. 0° 04' W., 6.42 chs. dist.
	Land, nearly level. Soil, loam, gravel and rocky. Undergrowth, shadscale.
	Point for the ½ sec. cor. of sec. 30, T. 29 N., R. 42 E., on the E. bdy. of T. 29 N., R. 41 E. and at midpoint on the W. bdy. of sec. 30.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.