

## DEPENDENT RESURVEY, SIXTH STANDARD PARALLEL NORTH, R. 43 E.

CHAINS

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,  
THROUGH R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
Hatch and Eaton, U. S. Deputy Surveyors, in 1869,  
the Resurvey Executed by  
H. B. Maxson, U. S. Deputy Surveyor, in 1893,  
and the Retracement and Partial Resurvey Executed by  
H. W. Reppert, U. S. Surveyor and A. T. Harris,  
U. S. Transitman, in 1914.

Beginning the resurvey at the standard cor. of T. 31 N.,  
Rs. 43 and 44 E., monumented with an iron post, 2½ ins.  
diam., set, mkd. and witnessed as described in the field  
notes of T. 31 N., R. 44 E., executed concurrently under  
this same Group.

N. 89° 34' W., along the S. bdy. of sec. 36.

Over gently rolling land, through medium undergrowth; asc.  
over a gradual E. slope.

- 7.50 Nevada State Highway No. 8A, bears N. 9¼° W. and S. 9¼°  
E.
- 9.80 Paved road, bears N. 71½° E., terminating at highway and  
S. 71½° W.
- 11.10 Telephone line, parallels paved road; asc. 20 ft. over a  
gradual E. slope.
- 19.80 Trail road, bears NE. and SW.; asc. 10 ft. over a gradual  
E. slope.
- 27.91 The closing cor. of T. 30 N., Rs. 43 and 44 E., herein-  
after described.
- Asc. 20 ft. over a gradual E. slope.
- 40.15 The standard ¼ sec. cor. of sec. 36, monumented with a  
mound of stone in a mound of earth. This point is  
locally recognized as the true corner point and is  
accepted as the best available evidence of the position  
of the original corner.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.  
in the ground and in a collar of stone, with brass cap  
mkd.
- SC  
T31N R43E  
¼ S 36
- 1967
- set a steel fence post, 6 ft. long, 2 ft. in the ground,  
alongside the iron post.