

DEPENDENT RESURVEY, SIXTH STANDARD PARALLEL NORTH, R. 43 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC

T31N R43E

¼ S 32

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

40.30 Water pipeline, underground, bears N. and S.

41.70 Trail road, bears N. and S.

49.60 Wash, 10 lks. wide, 1 ft. deep, drains SSW. into next wash.

51.00 Wash, 20 lks. wide, 1 ft. deep, drains SSE.

64.51 The ¼ sec. cor. of sec. 5, T. 30 N., R. 43 E., hereinafter described.

70.30 Wash, 20 lks. wide, 1 ft. deep, drains S.

80.28 The standard cor. of secs. 31 and 32, monumented with a granite stone, 6x5x4 ins., plainly mkd. with a cross (X) and 5 grooves on the E. face and firmly set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC

T31N R43E

S 31 | S 32

1967

bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

Land, gently rolling.

Soil, sandy clay loam and gravelly.

Undergrowth, shadscale, budsage and sagebrush.

N. 89° 55' W., along the S. bdy. of sec. 31.

Over gently rolling land, through medium undergrowth; desc. over a gradual SW. slope.

13.20 E. bank of Willow Creek, bears N. and S.; desc. 40 ft. over a W. slope.