DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 30 N., R. 43 E.

		T. 30 N., R. 43 E.
	CHAINS	
		T30N R43E
		½ S 1 S 12
		1967
		set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
	69.00	Telephone cable, underground, parallels power line.
	70.50	Power line, bears N. 62½° E. and S. 62½° W.
	77.00	Natural gas pipeline, bears N. $61\frac{1}{4}^{\circ}$ E. and S. $61\frac{1}{4}^{\circ}$ W.
	81.70	The cor. of secs. 1, 2, 11 and 12.
		Land, nearly level. Soil, sandy clay loam. Undergrowth, shadscale and budsage.
		N. 2° 26' E., bet. secs. 1 and 2.
	·	Over gently rolling land, through medium undergrowth; asc. a gradual SE. slope.
	9.60	Wash, 10 lks. wide, 3 ft. deep, drains ESE.; asc. 70 ft. over a gradual SE. slope.
	41.22	Point for the ½ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T30N R43E
		S 2 S 1
		'
		1967
		set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
		Asc. over a gradual SE. slope.
	48.40	Paved road, bears N. 71½° E. and S. 71½° W.
	49.00	Telephone line, parallels paved road; asc. 80 ft. over a gradual SE. slope.
	64.50	Wash, 10 lks. wide, 3 ft. deep, drains SSE.; asc. 70 ft. over a gradual SE. slope.
	82.73	Intersect the Sixth Standard Parallel North.
		Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
•		· ·