

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 43 E.

CHAINS

- 57.50 Spur, projects E.; desc. 60 ft. over a N. slope.
65.00 Bottom of descent; asc. 70 ft. over a gradual S. slope.
85.90 Intersect the Sixth Standard Parallel North.

Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N R43E
S 34
S 3 | S 2
T30N
CC

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner

The standard ¼ sec. cor. of sec. 34, bears S. 89° 53' W., 15.30 chs. dist.

Land, rolling.

Soil, sandy clay loam and rocky.

Undergrowth, shadscale and budsage.

The point for the N. ¼ sec. cor. of sec. 2 is on the Sixth Standard Parallel N. and at midpoint in departure on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N R43E
¼ S 2
T30N

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner

The angle point of secs. 2 and 35, bears N. 88° 58' W., 14.99 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.