

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 43 E.

CHAINS

74.30 Canal, dry, 30 lks. wide, 3 ft. deep, drains SW.; asc. 20 ft. over a gradual S. slope.

79.60 Graveled road, bears NW. and SE.

82.00 Telephone line, bears N. $54\frac{1}{2}^\circ$ W. and S. $54\frac{1}{2}^\circ$ E.

83.33 Intersect the Sixth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N	R43E
S 33	
S 4	S 3
T30N	
CC	

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner

The standard $\frac{1}{4}$ sec. cor. of sec. 33, bears S. $89^\circ 59'$ W., 15.54 chs. dist.

Land, gently rolling.
Soil, sandy clay loam.
Undergrowth, shadscale and budsage.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3 is on the Sixth Standard Parallel N. and at midpoint in departure on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N	R43E
$\frac{1}{4}$ S 3	
T30N	

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner

The standard cor. of secs. 33 and 34, bears N. $89^\circ 59'$ W., 15.325 chs. dist.