

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 43 E.

CHAINS	
76.30	Graveled road, parallels power line.
76.50	Water pipeline, underground, parallels power line.
80.88	The cor. of secs. 4, 5, 8 and 9. Land, gently rolling, sloping S. Soil, sandy clay loam. Undergrowth, shadscale and budsage.
	N. 3° 48' E., bet. secs. 4 and 5. Over gently rolling land, through medium undergrowth; asc. 60 ft. over a gradual S. slope.
35.60	Trail road, bears E. and W.; asc. 10 ft. over a gradual S. slope.
40.73	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T30N R43E S $5\frac{1}{2}$ S 4 1967 set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
43.60	Wash, 10 lks. wide, 1 ft. deep, drains SE.; asc. 10 ft. over a gradual S. slope.
44.60	Natural gas pipeline, underground, bears N. $68\frac{1}{2}^\circ$ W. and S. $68\frac{1}{2}^\circ$ E.; asc. 70 ft. over a gradual S. slope.
81.75	Intersect the Sixth Standard Parallel North. The closing cor. of secs. 4 and 5, monumented with a wooden post, 2x2x36 ins., dimly scribed and loosely set in a mound of stone on a mound of earth. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T31N R43E S 32 S 5 S 4 T30N CC 1967