

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 43 E.

CHAINS	
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 19' W., bet. secs. 5 and 6.
	Over gently rolling land, through medium undergrowth; asc. 20 ft. over a gradual SW. slope.
19.30	A channel of Willow Creek, dry, 10 lks. wide, 4 ft. deep, drains SSW.; asc. a gradual SW. slope.
28.90	Trail road, bears E. and W.; asc. a gradual SW. slope.
32.00	A channel of Willow Creek, dry, 20 lks. wide, 2 ft. deep, drains SW.; asc. a gradual S. slope.
40.31	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with the remains of a wooden post, loosely set in a mound of earth.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div>T30N R43E $\frac{1}{4}$ S 6 S 5 1967</div>
	reset the remains of the wooden post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
	<hr/>
	N. 8° 52' E., beginning new measurement.
	Asc. 10 ft. over a gradual S. slope.
4.70	Graveled road, bears E. and W.; asc. 80 ft. over a grad- ual S. slope.
37.00	Natural gas pipeline, underground, bears N. $68\frac{1}{2}^\circ$ W. and S. $68\frac{1}{2}^\circ$ E.; asc. a gradual S. slope.
43.63	Intersect the Sixth Standard Parallel North.
	Point for the closing cor. of secs. 5 and 6, at pro- portionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div>T31N R43E S 31 S 6 S 5 T30N CC 1967</div>