

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 30 N., R. 44 E.

CHAINS		
80.28	<p>Point for the cor. of secs. 25, 25, 36 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R44E R44½E S 25 S 25 S 36 S 36</p> <p style="text-align: center;">1968</p> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, sandy gravel. Undergrowth, shadscale, budsage and sagebrush.</p>	
	<p>N. 0° 38' E., bet. secs. 25 and 25.</p>	
	<p>Over gently rolling land, through medium undergrowth.</p>	
1.80	<p>Gravel road, bears S. 31° E. and N. 31° W.; desc. 120 ft. over a NW. slope.</p>	
40.14	<p>Point for the ¼ sec. cor. of secs. 25 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R44E R44½E ½ S 25 S 25</p> <p style="text-align: center;">1968</p> <p>raise a mound of stone, 2½ ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, the E. ¼ sec. cor. of sec. 25, T. 30 N., R. 44½ E., bears EAST, 0.84 chs. dist., hereinafter described.</p> <p>Desc. 100 ft. over a NW. slope to the sec. cor.</p>	
72.10	<p>Gravel road, bears SW. and NE.</p>	