

DEPENDENT RESURVEY OF A PORTION OF THE SIXTH STANDARD
PARALLEL NORTH, THROUGH R. 44 E.

CHAINS	<div>DEPENDENT RESURVEY OF A PORTION OF THE SIXTH STANDARD PARALLEL NORTH, THROUGH R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA.</div> <div>Reestablishment of a Portion of the Survey Executed by Hatch and Eaton, U. S. Deputy Surveyors, in 1869, and the Resurvey Executed by H. B. Maxson, U. S. Deputy Surveyor, in 1893.</div> <div>Beginning the resurvey at the standard cor. of T. 31 N., Rs. 44 and 45 E., monumented with the remains of a wooden post, loosely set in a mound of earth between the 4 original pits, the outlines of which are visible.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div>S C T31N R44E R45E <u>S 36 S 31</u></div> <div>1967</div> <div>reset the remains of the wooden post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</div> <div>from this corner</div> <div>A well, 9 ins. diam., bears N. 63° 36' W., 9.91 chs. dist.</div> <div>N. 89° 22' W., along the S. bdy. of sec. 36.</div> <div>Over nearly level land, through medium undergrowth; along S. side of fence, bears E. and W.</div> <div>27.80 Fence cor.; fences bear S. and E.</div> <div>40.11 The standard ¼ sec. cor. of sec. 36, monumented with a wooden post, 2x4x30 ins., dimly scribed and loosely set in a mound of earth.</div> <div>At the corner point</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div>S C T31N R44E <u>¼ S 36</u></div> <div>1967</div> <div>reset the wooden post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</div>
--------	--