

DEPENDENT RESURVEY OF A PORTION OF THE SIXTH STANDARD
PARALLEL NORTH, THROUGH R. 44 E.

CHAINS	
	<p>reset the wooden post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 20' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>25.20 Trail road, bears NNE. and SSW.</p> <p>40.12 The standard cor. of secs. 31 and 32, monumented with a wooden post, 2x3x30 ins., dimly scribed and loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R44E <u>S 31 S 32</u></p> <p style="text-align: center;">1967</p> <p>reset the wooden post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Undergrowth, greasewood, sagebrush and shadscale.</p>
	<p>N. 89° 16' W., along the S. bdy. of sec. 31.</p> <p>Over nearly level land, through medium undergrowth.</p> <p>19.70 Telephone cable, underground, parallels power line.</p> <p>21.10 Power line, bears N. 62½° E. and S. 62½° W.</p> <p>27.70 Natural gas pipeline, underground, bears N. 64° E. and S. 64° W.; trail road, bears N. and S.</p> <p>40.17 Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R44E <u>¼ S 31</u></p> <p style="text-align: center;">1967</p> <p>set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p>