

DEPENDENT RESURVEY OF A PORTION OF THE SIXTH STANDARD
PARALLEL NORTH, THROUGH R. 44 E.

CHAINS			
79.20	Trail road, bears NE. and SW.		
80.34	<p>The standard cor. of T. 31 N., Rs. 43 and 44 E., determined at the center point on a mound of earth between the 4 original pits, the outlines of which are clearly visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R43E R44E <u>S 36 S 31</u></p> <p style="text-align: center;">1967</p> <p>set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Undergrowth, greasewood and sagebrush.</p>		
	<p>DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 31 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA.</p>		
	<p>Reestablishment of a Portion of the Survey Executed by Hatch and Eaton, U. S. Deputy Surveyors, in 1869, and the Resurvey Executed by H. B. Maxson, U. S. Deputy Surveyor, in 1893.</p> <hr/> <p>From the standard cor. of T. 31 N., Rs. 44 and 45 E.</p> <p>N. 0° 29' E., bet. secs. 31 and 36.</p> <p>Over nearly level land, through scant undergrowth.</p> <td data-bbox="217 1755 371 1782">0.25</td> <td data-bbox="371 1755 1315 1782">Fence, bears E. and W.</td>	0.25	Fence, bears E. and W.
40.27	<p>The ¼ sec. cor. of secs. 31 and 36, monumented with a wooden post, 2x3x30 ins., dimly scribed and loosely set in a small mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T31N R44E R45E ¼ <u>S 36 S 31</u></p> <p style="text-align: center;">1967</p>		