

## DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY

T. 31 N., R. 44 E.

## CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T31N  
R43E R44E  
S 1  $\frac{S}{S}$   $\frac{6}{7}$

1967

bury the original corner stone alongside the iron post.

Land, low mountainous.

Soil, sandy clay loam and rocky.

Timber, scattered juniper.

Undergrowth, sagebrush, shadscale and budsage.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 31 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of a Portion of the Survey Executed by Hatch and Eaton, U. S. Deputy Surveyors, in 1869; Resurveyed by H. B. Maxson, U. S. Deputy Surveyor, in 1893, and H. W. Reppert, U. S. Surveyor, and A. T. Harris, U. S. Transitman, in 1914.

From the cor. of Tps. 31 and 32 N., Rs. 44 and 45 E.

N.  $89^{\circ} 54'$  W., bet. secs. 1 and 36.

Over nearly level land, through medium undergrowth.

20.30 Trail road, bears N. and S.

33.50 Base of ascent, bears N. and S.; asc. 160 ft. over an E. slope.

39.75 The  $\frac{1}{4}$  sec. cor. of sec. 1 only, monumented with a stone, 24x18x6 ins., plainly mkd.  $\frac{1}{4}$  on the S. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground to bedrock and in a mound of stone to cap,  $3\frac{1}{2}$  ft. base, with brass cap mkd.

T32N R44E

$\frac{1}{4}$  S 1  
T31N R44E

1971

Note: This cor. was set in 1966 and the brass cap was mkd. for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 36.

bury the original corner stone alongside the iron post.

N.  $89^{\circ} 47'$  W., beginning new measurement.

Over rolling land; asc. 20 ft. over an E. slope.

3.80 Ridge, bears N. and S.; desc. over a W. slope.