

DEPENDENT RESURVEY OF A PORTION OF THE
SIXTH STANDARD PARALLEL NORTH, R. 45 E.

CHAINS	
	Over gently rolling land, through medium undergrowth; desc. 50 ft. over a gradual W. slope.
30.60	The closing cor. of T. 30 N., Rs. 45 and 46 E., hereinafter described.
40.31	The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a granite stone, 15x7x6 ins., plainly mkd. SC $\frac{1}{4}$ on the N. face and firmly set with a mound of earth, N. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC R31N R45E <u>$\frac{1}{4}$ S 36</u></p>
	1967
	bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
	<p style="text-align: center;">_____</p> <p>S. 89° 39' W., beginning new measurement.</p>
	Over nearly level land.
15.80	Trail road, bears NE. and SW.
30.64	The $\frac{1}{4}$ sec. cor. of sec. 1, T. 30 N., R. 45 E., hereinafter described.
40.24	The standard cor. of secs. 35 and 36, monumented with a granite stone, 15x9x8 ins., plainly mkd. with 1 groove on the E. face, 5 grooves on the W. face, SC on the N. face and firmly set with a mound of earth, N. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">SC T31N R45E <u>S 35 S 36</u></p>
	1967