

DEPENDENT RESURVEY OF A PORTION OF THE
SOUTH BOUNDARY, T. 30 N., R. 45 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30N	R45E
S 31	S 32
S 6	S 5
T29N	

1967

bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

Land, mountainous.
Soil, sandy clay loam and rocky.
Undergrowth, sagebrush.

N. $89^{\circ} 39'$ W., bet. secs. 6 and 31.

Over mountainous land, through medium undergrowth; desc. 70 ft. over a SW. slope.

5.20 Creek, 10 lks. wide, 3 ft. deep, course NNW.; enter rolling land; desc. over a gradual W. slope.

9.70 Trail road, bears ESE. and WNW. into graveled road.

11.00 Graveled road, bears NW. and S.; desc. over a gradual W. slope.

14.20 Wash, 10 lks. wide, 2 ft. deep, drains N.; desc. 110 ft. over a gradual W. slope.

40.23 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a granite stone, 15x10x4 ins., dimly mkd. $\frac{1}{4}$ on the N. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30N	R45E
$\frac{1}{4}$ S 31	
S 6	
T29N	

1967

bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
