

DEPENDENT RESURVEY OF A PORTION OF THE
WEST BOUNDARY, T. 30 N., R. 46 E.

<p>CHAINS</p>	<p>reset the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 36, bears S. $89^{\circ} 44'$ W., 9.71 chs. dist.</p> <p>Land, gently rolling. Soil, sandy clay loam. Undergrowth, sagebrush, shadscale and budsage.</p>
	<p>DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, T. 30 N., R. 45 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of a Portion of the Survey Executed by Hatch and Eaton, U. S. Deputy Surveyors, in 1869, and the Purported Retracement and Partial Resurvey Executed by S. T. Morse, U. S. Deputy Surveyor, in 1901.</p> <hr/> <p>From the cor. of Tps. 29 and 30 N., R. 45 E.</p> <p>N. $0^{\circ} 07'$ E., along the W. bdy. of sec. 31.</p> <p>Over gently rolling land, through medium undergrowth; desc. over a gradual NW. slope.</p> <p>4.24 The closing cor. of Tps. 29 and 30 N., R. $44\frac{1}{2}$ E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the survey of T. 30 N., R. $44\frac{1}{2}$ E., executed under this same Group.</p> <p>7.60 Wash, 10 lks. wide, 1 ft. deep, drains WNW.; desc. over a gradual NW. slope.</p> <p>39.71 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with a quartz stone, $14 \times 10 \times 4$ ins., plainly mkd. $\frac{1}{4}$ on the W. face and firmly set in the ground. This cor. will now function as the $\frac{1}{4}$ sec. cor. of sec. 31 only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30N R44$\frac{1}{2}$E R45E $\frac{1}{4}$ S 31</p> </div> <p>1967</p> <p>bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <hr/>