

DEPENDENT RESURVEY OF A PORTION OF THE  
WEST BOUNDARY, T. 30 N., R. 45 E.

CHAINS	
38.70	Wash, 10 lks. wide, 2 ft. deep, drains NNW.; desc. over a gradual NW. slope.
41.95	The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented with a granite stone, 14x8x8 ins., plainly mkd. $\frac{1}{4}$ on the W. face and firmly set in the ground. This cor. will now function for the $\frac{1}{4}$ sec. cor. of sec. 30 only.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T30N R44<math>\frac{1}{2}</math>E R45E   <math>\frac{1}{4}</math> S 30</p>
	1967
	bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
	N. 0° 34' W., beginning new measurement.
	Desc. 100 ft. over a gradual NW. slope to the sec. cor.
2.745	The E. $\frac{1}{4}$ sec. cor. of sec. 25, T. 30 N., R. 44 $\frac{1}{2}$ E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the survey of T. 30 N., R. 44 $\frac{1}{2}$ E., executed under this same Group.
35.00	Graveled road, bears NE. and SW.
42.88	The cor. of secs. 24 and 25, R. 44 E., sec. 25, R. 44 $\frac{1}{2}$ E. and secs. 19 and 30, R. 45 E., at proportionate distance, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the survey of T. 30 N., R. 44 $\frac{1}{2}$ E., executed under this same Group.
	Land, gently rolling. Soil, sandy clay loam and gravelly. Undergrowth, sagebrush and shadscale.
	N. 0° 38' E., bet. secs. 19 and 24.
	Over gently rolling land, through medium undergrowth; desc. 30 ft. over a gradual NW. slope.