

DEPENDENT RESURVEY OF A PORTION OF THE
WEST BOUNDARY, T. 30 N., R. 45 E.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30N
R44E R45E
½
S 13 | S 18

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner

The chimney on a ranch house, bears S. 88° 03' E., 20.54 chs. dist.

80.16 The cor. of secs. 7, 12, 13 and 18, monumented with a wooden post, 1x1x18 ins., loosely set at cor. of fences, bearing N., S. and E. This point is locally recognized as the true corner point and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30N
R44E R45E
S 12 | S 7
S 13 | S 18

1967

Land, nearly level.
Soil, sandy clay loam.
Undergrowth, sagebrush and greasewood.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 45 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Surveys Executed by Hatch and Eaton, U. S. Deputy Surveyors, in 1869, and by Skinner, Garside and Preble, U. S. Deputy Surveyors, in 1873; the Survey and Partial Resurvey Executed by S. T. Morse, U. S. Deputy Surveyor, in 1901, and a Portion of the Retracement Executed by Guy Redwine, U. S. Surveyor, in 1913.