

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 45 E.

CHAINS

- 31.30 Wash, 10 lks, wide, 2 ft. deep, drains NNW.; asc. 30 ft. over a gradual N. slope.
- 40.16 The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with a granite stone, 10x8x4 ins., plainly mkd. $\frac{1}{4}$ on the N. face and firmly set in a mound of stone.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | |
|-----------------|------|
| T30N | R45E |
| $\frac{1}{4}$ S | 1 |
| $\frac{1}{4}$ S | 12 |
- 1967
- bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.
-
- N. $89^{\circ} 43'$ E., beginning new measurement.
- Asc. 10 ft. over a gradual N. slope.
- 8.00 Top of ascent on N. slope; desc. over a gradual N. slope.
- 8.70 Trail road, bears N. and S.; desc. 30 ft. over a gradual N. slope.
- 30.30 Bottom of descent; asc. 50 ft. over a gradual NW. slope.
- 40.26 Intersect the W. bdy. of T. 30 N., R. 46 E.
- The closing cor. of secs. 1 and 12, monumented with a granite stone, 16x10x6 ins., plainly mkd. with 1 groove on the N. face, 5 grooves on the S. face, CC on the W. face and firmly set in the ground with a mound of stone, W. of cor.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- | | | |
|------|------|-----|
| T30N | | |
| R45E | R46E | |
| CC S | 1 | S 7 |
| S | 12 | |
- 1967
- bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.