

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 45 E.

CHAINS

N. 0° 10' W., beginning new measurement.

Desc. over a gradual N. slope.

22.90 Trail road, bears ENE, and WSW.; desc. over a gradual N. slope.

46.67 Intersect the Sixth Standard Parallel North.

The closing cor. of secs. 1 and 2, monumented with a granite stone, 16x12x5 ins., plainly mkd. with 1 groove on the E. face, 5 grooves on the W. face, CC on the S. face and firmly set in the ground with a mound of earth, S. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N R45E
S 35
S 2 | S 1
T30N R45E
CC

1967

bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner the standard ¼ sec. cor. of sec. 35, bears S. 89° 50' W., 9.40 chs. dist.

Land, gently rolling.

Soil, sandy clay loam.

Undergrowth, shadscale, budsage, greasewood and sagebrush.

The point for the N. ¼ sec. cor. of sec. 1 is on the Sixth Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 1.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N R45E
¼ S 1
T30N R45E

1967

set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

From this corner the standard cor. of secs. 35 and 36, bears S. 89° 39' W., 9.60 chs. dist.