

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 45 E.

CHAINS		
	<p>bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 2 ft. base, 2 ft. high, N. of cor.</p> <hr/> <p>S. 89° 54' W., beginning new measurement.</p> <p>Asc. 40 ft. over a gradual N. slope.</p> <p>30.40 Wash, 10 lks. wide, 2 ft. deep, drains N.; over a gradual N. slope.</p> <p>40.15 The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, gently rolling. Soil, sandy clay loam and rocky. Undergrowth, sagebrush, shadscale and junegrass.</p>	
	<p>N. 1° 05' E., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through medium undergrowth; desc. 50 ft. over a gradual N. slope.</p> <p>20.50 Trail road, bears E. and W.; desc. over a gradual N. slope.</p> <p>23.30 Trail road, bears ENE. and WSW.; desc. 30 ft. over a gradual N. slope.</p> <p>39.72 The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a granite stone, 12x10x6 ins., plainly mkd. $\frac{1}{4}$ on the W. face and firmly set in the ground with a mound of earth, W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R45E $\frac{1}{4}$ S 3 S 2 1967</p>	
	<p>bury the original corner stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <hr/> <p>N. 1° 08' E., beginning new measurement.</p> <p>Desc. 40 ft. over a gradual N. slope.</p> <p>46.65 Intersect the Sixth Standard Parallel North.</p> <p>The closing cor. of secs. 2 and 3, monumented with a granite stone, 12x12x6 ins., plainly mkd. with 2 grooves on the E. face, 4 grooves on the W. face, CC on the S. face and firmly set in the ground.</p>	