SURVEY OF THE	SUBDIVISIONAL	LINES,	T.	17 N.,	R.	33₺	Ε.
---------------	---------------	--------	----	--------	----	-----	----

	SURVEY OF THE SUBDIVISIONAL LINES, T. 17 N., R. 33½ E.
CHAINS	WEST, bet. secs. 25 and 36.
	Over a gentle W. slope, through medium dense grass and scattered brush. Desc. 80 ft. to the 表 sec. cor.
40.00	Point for the ½ sec. cor. of secs. 25 and 36.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T17N R33½E ½ S 25 S 36
	1967
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	Desc. 30 ft. over a continued gentle W. slope.
64.70	Intersect the E. bdy. of T. 17 N., R. 33 E.
	Point for the closing cor. of secs. 25 and 36.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T17N R33E R33½E S 25 $\frac{S}{S}$ 25 CC
	1967
	raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	from this corner
	The cor. of secs. 25 and 36, T. 17 N., R. 33 E., bears SOUTH 9.98 chs. dist.
	Land, gently rolling. Soil, clay sand. Undergrowth, sagebrush and sandgrass.
	Point for the W. ½ sec. cor. of sec. 36, T. 17 N., R. 33½ E., at midpoint in latitude on the W. bdy. of sec. 36 and on the E. bdy. of T. 17 N., R. 33 E.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

1967