

SURVEY OF THE SOUTH BOUNDARY, T. 17 N., R. 34 E.

CHAINS	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, gently rolling. Soil, sandy clay and gravel. Undergrowth, sagebrush.
	WEST, bet. secs. 6 and 31. Over gently rolling land, through medium dense undergrowth.
35.90	Wash, 40 lks. wide, 1 ft. deep, drains WNW. from SE.; thence along wash.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, falls in wash. Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 6 and 31, bears SOUTH, 0.25 chs. dist. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div>WC T17N R34E $\frac{1}{4}$ S 31 S 6 T16N 1966</div>
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
44.00	Leave wash, drains WSW.
55.50	Wash, same, 60 lks. wide, 1 ft. deep, drains WNW.
61.30	Wash, 10 lks. wide, 1 ft. deep, drains NNW.
79.40	Point for the cor. of Tps. 16 and 17 N., Rs. $33\frac{1}{2}$ and 34 E., as instructed in the Special Instructions. This point is calculated to be NORTH of the theoretical position of the standard corner of T. 16 N., Rs. $33\frac{1}{2}$ and 34 E., which position is 480.00 chs. WEST of the standard corner of T. 16 N., Rs. 34 and 35 E. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div>T17N R33$\frac{1}{2}$E R34E S 36 S 31 S 1 S 6 T16N 1966</div>
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.