CHAINS	SURVEY OF THE SUBDIVISIONAL LINES OF T. 18 N., R. 34 E.
	Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to cap, with brass cap mkd.
	T18N R34E S 2
	COR 4 WH MS 2906
	1966
	bury the remains of the pine post along- side the iron post.
	Desc. 40 ft. over a WNW. slope.
39.00	Shallow ravine, drains W.; over a rocky W. slope.
40.00	Point for the 1/2 sec. cor. of secs. 1 and 2.
·	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in rock and in a mound of stone, 4 ft. base to cap, with brass cap mkd.
	T18N R34E
	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
	1966
	Asc. 40 ft. over a rocky W. slope.
43.50	Spur, slopes NW.; desc. 100 ft. over a NNE. slope.
47.30	Ravine, drains WNW.; asc. 30 ft. over a S. slope.
49.20	Spur, slopes WNW.; desc. 130 ft. over a broken WNW. slope.
63.50	Wash, 10 1ks. wide, 1 ft. deep, drains WNW.; asc. 40 ft. over a SW. slope.
66.60	Low spur, slopes NW.; desc. 80 ft. over a broken N. slope
75.50	Wash, 120 1ks. wide, 2 ft. deep, drains W.; asc. 70 ft. over a S. slope.
80.07	Intersect the S. bdy. of T. 19 N., R. 34 E.
	Point for the closing cor. of secs. 1 and 2.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd.