

SURVEY OF THE WEST BOUNDARY OF T. 19 N., R. 34 E.

| CHAINS | |
|--------|--|
| | NORTH, bet. secs. 1 and 6. |
| | Asc. 40 ft. over a continued SE. slope, through sparse undergrowth. |
| 2.80 | Narrow rocky ridge, bears NE. and SW.; desc. 100 ft. over a NW. slope. |
| 5.00 | Ravine, drains NNE.; desc. 80 ft. over a rolling E. slope. |
| 12.00 | Same ravine, drains NE. from SSE.; asc. 100 ft. over a rolling SE. slope changing to SSE. |
| 20.00 | Low spur, slopes E.; desc. 30 ft. over a broken E. slope. |
| 31.80 | Canyon rim, bears E. and W.; desc. 60 ft. over a steep N. slope. |
| 33.40 | Base of steep descent, bears E. and W.; across flood channeled canyon bottom, draining E. |
| 34.50 | Wash, 15 lks. wide, 1 ft. deep, drains E. |
| 34.80 | Dim track road, bears E. and W. |
| 39.90 | Leave canyon bottom, bears E. and W.; over a S. slope. |
| 40.00 | Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6. |
| | Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. |
| | <div style="text-align: center;"> T19N R33$\frac{1}{2}$E R34E $\frac{1}{4}$ S 1. S 6 </div> |
| | 1967 |
| | raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor. |
| | Continue asc. over S. slope. |
| 40.40 | Low rim, 15 ft. above canyon bottom, bears E. and W.; along a gentle E. slope. |
| 41.30 | Trail road, bears E. and W.; asc. 110 ft. over a rolling ESE. slope. |
| 57.20 | Prominent earthquake fault, bears NNE. and SSW.; asc. 250 ft. over a continued rolling ESE. slope. |
| 68.80 | Top of ascent on a steep E. slope; desc. 130 ft. over a rolling E. slope. |