

SURVEY OF THE SUBDIVISIONAL LINES OF T. 19 N., R. 34 E.

CHAINS	
	Land, gently rolling. Soil, sandy clay with gravel. Undergrowth, sagebrush and shadscale.
	N. 0° 03' E., bet. secs. 1 and 2.
	Desc. 50 ft. over gently rolling land draining NW., through medium dense undergrowth.
40.00	Point for the ¼ sec. cor. of secs. 1 and 2. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T19N R34E S 2 ½ S 1 1967 raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Desc. 50 ft. over a continued NW. slope to the sec. cor.
40.50	Wash, 20 lks. wide, 3 ft. deep, drains NW.
47.70	Wash, 40 lks. wide, 3 ft. deep, drains NW.
66.80	Bladed trail road, bears ENE. and WSW.
79.90	Wash, 30 lks. wide, 5 ft. deep, drains NW.
80.15	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. The wash SW. of the cor. has enlarged greatly, jeopardizing the security of the monument. I rehabili- tate the monument, placing a collar of stone around the iron post. from which: An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, and in a collar of stone, for a reference monument, bears N. 75° E., 66.0 ft. dist., with brass cap mkd. T20N R34E S36 RM 66.0 FT. 1967, with an arrow pointing to the true corner point. An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, and in a collar of stone, for a reference monument, bears N. 15° W., 66.0 ft. dist., with brass cap mkd. T20N R34E S35 RM 66.0 FT. 1967, with an arrow pointing to the true corner point.