INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH, RANGE 35 EAST

 	KANGE 33 EAST
CHAINS	INDEPENDENT RESURVEY OF THE THIRD STANDARD PARALLEL NORTH, THROUGH RANGE 35 EAST
	This Independent Resurvey Supersedes the Survey Executed by T. K. Stewart, U. S. Deputy Surveyor, in 1884. A diligent search was made for the original corners and none were found.
	Beginning at the standard cor. of Tp. 16 N., Rs. 35 and 36 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 16 N., R. 36 E., surveyed concurrently under Grp. No. 437.
	WEST, along the S. bdy. of sec. 36.
	Over mountainous terrain, through medium dense undergrowth; asc. 180 ft. along a gently rolling S. slope, gradually changing to an ESE. slope.
2 6.00	Low ridge, at saddle, bears N. and S.; desc. 40 ft. along a rolling N. slope.
37.20	Ravine, drains N.; asc. 50 ft. over a steep NNE. slope.
40.00	Point for the standard ½ sec. cor. of sec. 36.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SC T16N R35E ½ S 36
	1966
•	raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.
	Asc. 50 ft. over a NNE. slope, changing to a N. slope.
44.20	Top of ascent on N. slope; desc. 320 ft. over a NNW. slope, changing to a NW. slope.
60.10	Shallow ravine, drains NW.; asc. 30 ft. over a NE. slope.
66.80	Spur, slopes NW.; desc. 120 ft. over a SW. slope.
73.00	Shallow ravine, drains NW.; desc. 40 ft. over a W. slope.
80.00	Point for the standard cor. of secs. 35 and 36.
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to cap, with brass cap mkd.