		DEPENDENT RESURVEY, E. BDY., T. 32 N., R. 34 E.
	CHAINS	
	79. 50	Interstate highway No. 80, W. bound lane, bears N. 70° E. and S. 70° W.
	80.20	The cor. of Tps. 32 and 33 N., R. 34 and 34½ E., monumented with a copper-coated steel stake, buried 18 ins. below the surface of the road, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 33 N., R. 34 E., executed under this same Group.
		From this corner, a witness point, bears N. 1° 29' W., 2.18 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the resurvey of T. 33 N., R. 34 E., executed concurrently under this same Group.
	,	Land, nearly level. Soil, sandy loam. Undergrowth, shadscale and greasewood.
		From the cor. of secs. 1, 1, 12 and 12, on the E. bdy. of the Tp.
		SOUTH, bet. secs. 12 and 12.
		Over nearly level land, through medium undergrowth.
	40.00	Point for the \$\frac{1}{4}\$ sec. cor. of secs. 7 and 12, now the \$\frac{1}{4}\$ sec. cor. of secs. 12 and 12, at record distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T32N R34E R34½E \$ 12 S 12
l		1967
		set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
	49 .2 0	Trail road, bears NE. and SW.; asc. 30 ft. over a gentle N. slope.
	7 2. 50	Trail road, bears ENE. and WSW.; asc. 20 ft. over a gentle N. slope.
	76.00	Trail road, bears NE. and SW.
	77.47	Intersect the N. bdy. of sec. 13, T. 32 N., R. 34 E.
		Point for the closing cor. of secs. 12 and 12.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.