

SURVEY OF THE SUBDIVISION, T. 32 N., R. 34½ E.

CHAINS

20.04

From the cor. of secs. 1, 1, 12 and 12 on the W. bdy. of the Tp.


EAST, bet. secs. 1 and 12.

Over nearly level land, through medium undergrowth.

Intersect the W. bdy. of sec. 8, T. 32 N., R. 35 E.

Point for the closing cor. of secs. 1 and 12, T. 32 N., R. 34½ E.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



1967

set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post.

From this corner, the W. ¼ sec. cor. of sec. 8, T. 32 N., R. 35 E., bears N. 0° 52' E., 5.51 chs. dist., heretofore described.

From this same corner, the cor. of secs. 8 and 17, T. 32 N., R. 35 E., bears S. 0° 52' W., 34.79 chs. dist., heretofore described.


Land, nearly level.

Soil, sandy loam.

Undergrowth, shadscale, greasewood and sagebrush.

The point for the E. ¼ sec. cor. of sec. 12 at a point EAST of the W. ¼ sec. cor. of sec. 12 and on the W. bdy. of sec. 17, T. 32 N., R. 35 E.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



1967

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, the cor. of secs. 8 and 17, T. 32 N., R. 35 E., bears N. 0° 30' E., 5.21 chs. dist., heretofore described.