

DEPENDENT RESURVEY, SOUTH BOUNDARY, T. 34 N., R. 35 E.

CHAINS	
37.94	<p>The cor. of Tps. 33 and 34 N., Rs. 34 and 35 E., established under Contract No. 5 in 1867, monumented with a basalt stone, 18x8x8 ins., firmly set in a small mound of stone and plainly mkd. 6 notches on the N., E., S. and W. edges of the stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div><div>T34N</div><div>R34E R35E</div><div>S 36 S 31</div><div>S 37 S 6</div><div>T33N</div></div> <p>1966</p> <p>bury the original corner stone and set a steel fence post, 7 ft. long, 2½ ft. in the ground, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy loam. Undergrowth, shadscale.</p>
	<p>DEPENDENT RESURVEY OF THE HUMBOLDT RIVER GUIDE MERIDIAN, ALONG THE EAST BOUNDARY, T. 34 N., R. 35 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>Reestablishment of the Survey Executed by W. Epler, U. S. Deputy Surveyor, in 1867</p> <hr/>
	<p>From the cor. of Tps. 33 and 34 N., Rs. 35 and 36 E. N. 0° 19' E., bet. secs. 31 and 36.</p> <p>Over rolling land, along W. slope, through medium undergrowth.</p>
2.70	Ravine, drains WSW.; asc. 20 ft. over a W. slope.
5.00	Spur, slopes W.
10.60	Ravine, drains WNW.; desc. 50 ft. over a WNW. slope.
18.20	Ravine, drains W.; asc. 60 ft. over a SW. slope.
22.30	Spur, slopes W.; desc. 20 ft. over a WNW. slope.
25.10	Ravine, drains WNW.; desc. 70 ft. over a WNW. slope.
34.40	Ravine, drains NW.; desc. 20 ft. over a WNW. slope.
36.80	Slope changes to N.; desc. 30 ft. over a N. slope.