

DEPENDENT RESURVEY, WEST BOUNDARY, T. 34 N., R. 35 E.

CHAINS

bury the corner stone, reset the wooden post and set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post.

N. 0° 12' W., beginning new measurement.

Over an E. slope, through medium undergrowth.

- 7.50 Trail road, bears NW. and SE.
- 15.70 Trail road, bears E. and W.
- 19.20 Mill Creek, dry, 40 lks. wide, 4 ft. deep, drains E.; asc. 60 ft. over a gradual S. slope.
- 31.70 Spur, slopes ENE.; desc. 60 ft. over a N. slope.
- 39.24 The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record, executed under Group No. 123.

Land, gently rolling.
Soil, sandy loam and gravelly.
Undergrowth, shadscale, budsage and sagebrush.

N. 0° 01' W., bet. secs. 1 and 6.

Over rolling land, through medium undergrowth; desc. 10 ft. over a N. slope.

- 1.40 Wash, 10 lks. wide, 1 ft. deep; drains ENE.; asc. 20 ft. over a SE. slope.
- 5.20 Spur, slopes E.; desc. 30 ft. over a N. slope.
- 16.90 Trail road at bottom of descent, bears NE. and SW.; asc. 10 ft. over a gradual SE. slope.
- 24.70 Trail road, bears ENE. and WSW.; asc. 20 ft. over a gradual SE. slope.
- 37.20 Top of ascent on E. slope; desc. 20 ft. over an E. slope.
- 40.14 The ¼ sec. cor. of secs. 1 and 6, monumented with a stone, 16x12x10 ins., firmly set and plainly mkd. ¼ on the W. face.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T34N
R34E R35E
½
S 1 | S 6

1966