

DEPENDENT RESURVEY, W. BDY., T. 3 S., R. 69 E.

CHAINS										
	<p>N. 0° 05' W., beginning new measurement.</p> <p>Desc. 70 ft. over a rolling N. slope, through dense timber.</p> <p>40.00 The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 16x14x10 ins., mkd. 5 notches on the S. edge and 1 notch on the N. edge, firmly set in the ground.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T3S</td></tr> <tr><td colspan="2" style="text-align: center;">R68E R69E</td></tr> <tr><td style="text-align: center;">S 1</td><td style="text-align: center;">S 6</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> </table> <p style="text-align: center;">1968</p> <p>from which the original bearing trees</p> <p>A juniper, 20 ins. diam., bears N. 9¼° E., 185 lks. dist., mkd. T3S R69E S6 BT.</p> <p>A juniper, 14 ins. diam., bears S. 59° W., 87 lks. dist., mkd. T3S R68E S12 BT.</p> <p>A juniper, 10 ins. diam., bears N. 79¼° W., 63 lks. dist., mkd. T3S R68E S1 BT.</p> <p>bury the original cornerstone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>Land, rolling. Soil, clay and gravel. Timber, juniper and pinon. Undergrowth, sagebrush and scrub oak.</p>	T3S		R68E R69E		S 1	S 6	S 12	S 7	
T3S										
R68E R69E										
S 1	S 6									
S 12	S 7									
	<p>N. 0° 19' W., bet. secs. 1 and 6.</p> <p>Desc. 20 ft. over a N. slope, through scattered timber.</p> <p>2.50 Head of small wash, drains NE.; along a rolling W. slope.</p> <p>32.00 Wash, 100 lks. wide, 3 ft. deep, drains W.; asc. 80 ft. over a S. slope.</p> <p>39.96 The ¼ sec. cor. of secs. 1 and 6, monumented with a granite stone, 16x8x4 ins., mkd. ¼ on the W. face and firmly set in a mound of stone.</p> <p>At the corner point</p>									