

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BDY.
T. 13 N., R. 66 E.

CHAINS							
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R66E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">WC</td> </tr> <tr> <td colspan="3" style="text-align: center; border-top: 1px solid black;">T13N R66E</td> </tr> </table> <p style="text-align: center;">1966</p> <p>raise a mound of stone, 4 ft. base, 2½ ft. high, S. of cor.</p>	S 6	S 5	WC	T13N R66E		
S 6	S 5	WC					
T13N R66E							
3.40	Telephone line, bears NW. and SE.						
3.90	Wash, 30 lks. wide, 4 ft. deep, drains SSE.; asc. 200 ft. over E. slope.						
18.40	Top of spur, slopes S.; desc. 50 ft. over W. slope.						
22.90	Wash, 15 lks. wide, 3 ft. deep, drains S.; asc. 140 ft. over E. slope.						
23.60	Road, semi-improved, bears N. and S.						
37.50	Top of spur, slopes N.; desc. 20 ft. over NW. slope.						
42.80	Wash, 20 lks. wide, 1 ft. deep, drains NNE.; asc. 100 ft. over ESE. slope.						
45.18	<p>Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance. There is no remaining evidence of the original corner. This point will now serve as the ¼ sec. cor. of sec. 6, T. 13 N., R. 66 E., only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R66E</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td colspan="2" style="text-align: center; border-top: 1px solid black;">T13N R66E</td> </tr> </table> <p style="text-align: center;">1966</p> <p>raise a mound of stone, 3½ ft. base, 2½ ft. high, S. of cor.</p>	¼	S 6	T13N R66E			
¼	S 6						
T13N R66E							
54.60	Top of spur, slopes S.; desc. 40 ft. over W. slope.						
56.70	Wash, 40 lks. wide, 1 ft. deep, drains S.						
58.00	Wash, 20 lks. wide, 1 ft. deep, drains S.; asc. 150 ft. over E. slope.						
67.46	From this point, BLM tellurometer station, U-44-4, set under Grp. No. 389, monumented with a copper weld, 1 in. diam., firmly set, bears South, 0.35 chs. dist.						
67.50	Top of spur, slopes S.; desc. 120 ft. over W. slope.						