

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 60 E.

CHAINS	
	Over nearly level land, through medium undergrowth.
18.00	Trail road, bears SSE. and NNW.
39.54	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T30N R60E $\frac{1}{4}$ S $\frac{1}{12}$ 1967 raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
67.50	Trail road, bears NW. and SE.
79.08	The cor. of secs. 1, 2, 11 and 12. Land, nearly level. Soil, sandy clay. Undergrowth, sagebrush.
	N. $0^{\circ} 48'$ W., bet. secs. 1 and 2. Over nearly level land, through medium undergrowth.
13.70	Unimproved road, bears W. and E., 1.50 chs. dist. to fork of road, thence ESE. and ENE.
40.15	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T30N R60E $\frac{1}{4}$ S 2 S 1 1967 raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
78.09	Intersect the Sixth Standard Parallel North. Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.