DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 30 N., R. 60 E.

CHAINS

78.59 | Intersect the Sixth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

1967

set a steel fence post alongside the iron post.

From this corner, the standard cor. of secs. 33 and 34, bears S. 89° 54' E., 18.48 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the resurvey of the Sixth Standard Parallel North, through R. 60 E., executed under this same Group.

Land, nearly level.
Soil, sandy clay.
Undergrowth, crested wheatgrass.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, on the Sixth Standard Parallel North and at midpoint on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

表 S 3 T30N R60E

1967

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of cor.

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 34, bears S. 89° 41' E., 18.86 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the resurvey of the Sixth Standard Parallel North, through R. 60 E., executed under this same Group.