

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 60 EAST

CHAINS	<p>S. 89° 55' W., along the S. bdy. of sec. 36.</p> <p>Over nearly level land, through medium undergrowth.</p> <p>21.62 The closing cor. of T. 30 N., Rs. 60 and 61 E., monu- mented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 30 N., R. 60 E., executed concurrently under this same Group.</p> <p>41.18 The standard ¼ sec. cor. of sec. 36, monumented with a deteriorated wooden post, 16 ins. long, 2 ins. diam., loosely set in a small mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div>SC T31N R60E ¼ S 36</div> <p>1967</p> <p>bury the original wooden post and set a steel fence post alongside the iron post.</p> <hr/> <p>N. 89° 00' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>19.90 Trail road, bears NNW. and SSE.</p> <p>20.195 The ¼ sec. cor. of sec. 1, T. 30 N., R. 60 E., monu- mented with an iron post, 2½ ins. diam., set, mkd, and witnessed as described in the field notes of T. 30 N., R. 60 E., executed concurrently under this same Group.</p> <p>39.64 The standard cor. of secs. 35 and 36, monumented with a wooden post, 18 ins. long, 1 in. diam., loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div>SC T31N R60E S 35   S 36</div> <p>1967</p> <p>bury the original wooden post and set a steel fence post alongside the iron post.</p>
--------	---