

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,
THROUGH RANGE 60 EAST

| CHAINS | |
|--------|---|
| 37.80 | Franklin River, 20 lks. wide, 2 ft. deep, drains W. 2.00 chs. dist., thence SW. |
| 40.10 | <p>Point for the standard $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R60E <u>$\frac{1}{4}$ S 32</u></p> <p style="text-align: center;">1967</p> <p>set a steel fence post alongside the iron post.</p> |
| 56.375 | The $\frac{1}{4}$ sec. cor. of sec. 5, T. 30 N., R. 60 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 30 N., R. 60 E., executed concurrently under this same Group. |
| 80.20 | <p>The standard cor. of secs. 31 and 32, monumented with a deteriorated wooden post, 28 ins. long, 1 in. diam., loosely set in a small mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T31N R60E <u>S 31 S 32</u></p> <p style="text-align: center;">1967</p> <p>bury the original wooden post and set a steel fence post alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, sagebrush and yellowtop.</p> |
| | <p>N. $89^{\circ} 47'$ W., along the S. bdy. of sec. 31.</p> <p>Over nearly level land, through medium undergrowth.</p> |
| 11.70 | Trail road, bears NW. and SE. |
| 14.92 | The closing cor. of secs. 5 and 6, T. 30 N., R. 60 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of T. 30 N., R. 60 E., executed concurrently under this same Group. |