

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,  
THROUGH R. 61 E.

CHAINS

Reestablishment of the Survey Executed by  
Smyles and Preble, U. S. Deputy Surveyors, in 1880.

From the standard cor. of T. 31 N., Rs. 61 and 62 E.,  
monumented with a wooden post, 18 ins. long, 1 in. diam.,  
dimly scribed and set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.  
in the ground to bedrock and in a mound of stone, 3½ ft.  
base to top, with brass cap mkd.

SC  
T31N  
R61E R62E  
S 36 | S 31

1967

bury the wooden post alongside the iron post.

S. 89° 39' W., along the S. bdy. of sec. 36.

Over rolling land, through scattered timber; desc. 20 ft.  
over a W. slope.

8.00 Trail road in bottom of draw draining SSE., bears SE. and  
NW.; asc. 120 ft. over an E. slope.

18.00 Spur, slopes SW.; desc. 30 ft. over a W. slope.

21.00 Draw, drains SW.; asc. 30 ft. over an E. slope.

24.87 The closing cor. of secs. 1 and 6, T. 30 N., Rs. 61 and  
62 E., hereinafter described.

26.50 Spur, slopes SSW.; desc. 60 ft. over a W. slope.

31.30 Draw, drains SSW.; asc. 90 ft. over a SE. slope.

40.05 Point for the standard ¼ sec. cor. of sec. 36, at pro-  
portionate distance; there is no remaining evidence of  
the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in  
the ground to bedrock and in a mound of stone, 3 ft.  
base to top, with brass cap mkd.

SC  
T31N R61E  
¼ S 36

1967