

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,
THROUGH R. 61 E.

CHAINS

SC
T31N R61E
S 31 | S 32

1967

bury the wooden post and set the steel fence post along-
side the iron post.

Land, gently rolling.

Soil, sandy clay.

Undergrowth, sagebrush.

N. 89° 31' W., along the S. bdy. of sec. 31.

Over gently rolling land, through medium undergrowth.

23.52 The closing cor. of secs. 5 and 6, T. 30 N., R. 61 E.,
hereinafter described.

39.04 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

SC
T31N R61E
 $\frac{1}{4}$ S 31

1967

raise a mound of stone, 3 ft. base, 2 ft. high, N. of
cor.

63.15 The $\frac{1}{4}$ sec. cor. of sec. 6, T. 30 N., R. 61 E., herein-
after described.

78.08 The standard cor. of T. 31 N., Rs. 60 and 61 E., monu-
mented with a deteriorated wooden post, 14 ins. long, 1
in. diam., loosely set in a small mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

SC
T31N
R60E R61E
S 36 | S 31

1967