

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 30 N., R. 61 E.

CHAINS

79.92 The cor. of secs. 3, 4, 9 and 10.

Land, gently rolling.
Soil, sandy clay.
Timber, scattered juniper and pinon.
Undergrowth, sagebrush.

N. 1° 58' W., bet. secs. 3 and 4.

Over gently rolling land, through medium undergrowth.

39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T30N R61E

	$\frac{1}{4}$	
S 4		S 3

1967

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

78.23 Intersect the Sixth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T31N R61E

S	33	
S 4		S 3

T30N R61E

CC

1967

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 33, bears N. 89° 13' W., 15.20 chs. dist.

Land, gently rolling.
Soil, sandy clay and light gravel.
Undergrowth, sagebrush.

The point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, on the Sixth Standard Parallel North and at midpoint on the N. bdy. of sec. 3.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.