

TOWNSHIP 16 NORTH, RANGE 63 EAST

CHAINS

The geographic position for the southeast corner of the township is at latitude $39^{\circ} 12' 05.6''$ N., and longitude $114^{\circ} 49' 22.4''$ W. as calculated from U.S.C. & G.S. bench mark, R 42, located in section 1, T. 15 N., R. 63 E.

The magnetic declination was read at a number of stations throughout the township and the average of these readings was found to be 17° E.

DEPENDENT RESURVEY OF A PORTION OF THE THIRD STANDARD
PARALLEL NORTH, THROUGH RANGE 63 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by Monroe and
Bateman, U. S. Deputy Surveyors, in 1871.

The standard cor. of T. 16 N., Rs. 63 and 64 E., monumented with the remains of a wooden post, 3 ins. diam., set at the cor. of fences, from which fences bear E., S. and W.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T16N
R63E R64E
S 36 | S 31

1967

reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. $89^{\circ} 43'$ W., along the S. bdy. of sec. 36.

Over gradual E. slope, through medium undergrowth; asc. 40 ft. along a fence.

20.08 Point for the standard E. 1/16 sec. cor. of sec. 36, at midpoint.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T16N R63E
E1/16 S 36

1967

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

20.20 Fence corner, from which fences bear N., E. and S., bears SOUTH, 8 lks. dist.