

## DEPENDENT RESURVEY, THIRD STANDARD PARALLEL NORTH, R. 63 E.

CHAINS	
40.28	<p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>The standard cor. of secs. 33 and 34, monumented with a wooden post, 24 ins. long, 2 ins. square, mkd. TXVIN RLXIIIE SXXXIII SXXXIV and loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T16N R63E S 33   S 34</p> <p style="text-align: center;">1967</p> <p>reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Land, rolling. Soil, sandy clay and gravelly. Timber, juniper and pinon. Undergrowth, sagebrush.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY OF T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by Monroe and Bateman, U. S. Deputy Surveyors, in 1872.</p> <hr/> <p>From the standard cor. of T. 16 N., Rs. 63 and 64 E. N. 0° 05' W., bet. secs. 31 and 36.</p> <p>Over nearly level land, through medium undergrowth.</p>
20.02	<p>Point for the S. 1/16 sec. cor. of secs. 31 and 36, at midpoint.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R63E R64E S 1/16 S 36   S 31</p> <p style="text-align: center;">1967</p>
32.60	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Diversion ditch, drains NW.</p>
40.04	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>