

DEPENDENT RESURVEY, SUBDIVISIONAL LINES, T. 16 N., R. 63 E.

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES OF T. 16 N., R. 63 E.,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Surveys Executed by
Monroe and Bateman, U. S. Deputy Surveyors, in 1872
and W. N. McGill, U. S. Deputy Surveyor, in 1878.

From the standard cor. of secs. 35 and 36, on the S. bdy.
of the Tp.

N. $0^{\circ} 16'$ W., bet. secs. 35 and 36.

Over gently rolling land, through scattered undergrowth.

19.785 Point for the S. 1/16 sec. cor. of secs. 35 and 36, at
midpoint.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T16N R63E
S 1/16
S 35 | S 36

1967

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

20.50 Improved gravel road, bears E. and W.

39.57 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T16N R63E
 $\frac{1}{4}$
S 35 | S 36

1967

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

59.355 Point for the N. 1/16 sec. cor. of secs. 35 and 36, at
midpoint.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in
the ground and in a collar of stone, with brass cap mkd.

T16N R63E
N 1/16
S 35 | S 36

1967